


REV.	DESCRIPTION	DATE	DR.	APVD.
Α	ISSUED	04/23/2019	YS	DS

ELLIPTICAL SWAGE INSTALLATION PROCEDURE FOR TERMINALS



1. THE NAME, "ELLIPTICAL SWAGE" FAIRLY WELL DESCRIBES WHAT IS HAPPENING TO THE PART. THE ELLIPTICAL SWAGING OPERATION FORMS THE LIPS OF THE SHANK INTO A ELLIPTICAL SHAPE. THE TOOL THAT DOES THE ACTUAL FORMING IS CALLED THE "ELLIPTICAL PUNCH". THE TOOL THAT SUPPORTS THE TERMINAL WHILE SWAGING IS BEING DONE IS CALLED THE "ANVIL" (ALSO SOMETIMES CALLED THE "SEAT")

2. PLACE PROPER CONCORD'S ANVIL AND PUNCH INTO ARBOR PRESS AND ALIGN TOOLS PRIOR SWAGE FORCE.

- 3. DRILL A HOLE IN THE BOARD THAT IS JUST LARGE ENOUGH FOR THE SHANK OF THE TERMINAL TO PASS THROUGH, BUT NOT LARGE ENOUGH FOR THE SHOULDER TO PASS THROUGH (SEE INDIVIDUAL PART SPECIFICATIONS FOR RECOMMENDED HOLE SIZE).
- 4. PLACE A TERMINAL INTO THE ANVIL AND BOARD AS SHOWN.
- 5. PRESS TERMINAL USING PUNCH TOOL UNTIL LIP OF SHANK, WHICH EXTENDS PASSED THE FACE OF THE BOARD IS FORMED TO ELLIPTICAL SHAPE.
- 6. RASE THE PUNCH TOOL. TERMINAL IS NOW PERMANENTLY IN PLACE.

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES

TOLERANCES:

THREE PLACE DECIMAL ±0.010 FRACTIONAL ±1/64

PROPRIEIARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN
THIS DRAWING IS THE SOLE
PROPERTY OF CONCORD
ELECTRONICS INC. ANY
REPRODUCTION IN PART OR AS A
WHOLE WITHOUT THE WRITTEN
PERMISSION OF CONCORD
ELECTRONIC INC. IS PROHIBITED.



ELECTRONICS, INC.

TITLE

GENERIC DRAWING OF INSTALLATION TOOLS FOR ELLIPTICAL SWAGING (TA & TXP TYPES), ARBOR PRESS OPERATED

DWG. NO.

TA & TXP

A REV

PAGE: 2 OF 2

SCALE: NTS