


<b>DRAWING NUMBER:</b>	<b>09-0163-X-XX</b>
<b>PRODUCT GROUP:</b>	TERMINALS
<b>SUB-GROUP:</b>	COMMERCIAL NON-INSULATED TERMINALS
<b>DESCRIPTION:</b>	NON-INSULATED FEED THRU TERMINAL



BOARD / PANEL MOUNTING METHOD	MOUNTING HOLE SIZE	DRILL SIZE	FEED THRU COMBINATION
THREAD MOUNT (4-40 NUT)	0.120" ± 0.002	#31	SLOTTED/PIN

### PART NO. STRUCTURE:

09-0163 - X - XX  
 PART SERIES    DIMENSION    FINISH

### MATERIAL OPTIONS:

09-0163-X-XX

COMPONENT	MATERIAL	MATERIAL AND SPECIFICATION
TERMINAL	BRASS	BRASS PER ASTM B16, ALLOY C36000, 1/2 HARD

### DIMENSION OPTIONS:

09-0163-X-XX

DIMENSION	A	D	PIN DIAMETER	OVERALL LENGTH	SHANK LENGTH (L)	BOARD/PANEL THICKNESS
3	N/A	0.125"	0.033" ± 0.005	0.468"	N/A	UP TO 1/32"
4	N/A	0.156"	0.033" ± 0.005	0.500"	N/A	UP TO 1/16"
6	N/A	0.187"	0.033" ± 0.005	0.531"	N/A	UP TO 3/32"

FINISH - PLATING OPTIONS:

09-0163-X-**XX**

FINISH CODE	COMPONENT	FINISH	FINISH AND SPECIFICATION
01	TERMINAL	SILVER	0.000300"MIN. SILVER PER ASTM B700, TYPE 2, GRADE D WITH A NON-CHROMATE PRESERVATIVE TREATMENT
03	TERMINAL	GOLD	0.000010"MIN. GOLD PER ASTM B488, TYPE II, CODE C OVER 0.000050"MIN. NICKEL PER SAE-AMS-QQ-N-290
035	TERMINAL	GOLD	0.000050"MIN. GOLD PER ASTM B488, TYPE II, CODE C OVER 0.000050"MIN. NICKEL PER SAE-AMS-QQ-N-290
04	TERMINAL	ELECTRO-TIN	0.000300"MIN. ELECTRO-TIN PER ASTM B545 OVER 0.000100"MIN. COPPER PER SAE-AMS-2418
044	TERMINAL	BRIGHT ELECTRO-TIN	0.000300"MIN. BRIGHT ELECTRO-TIN PER ASTM B545 OVER 0.000100"MIN. COPPER PER SAE-AMS-2418
05	TERMINAL	ELECTRO-SOLDER	0.000300"MIN. ELECTRO-SOLDER PER SAE-AMS-P-81728 OVER 0.000100"MIN. COPPER PER SAE-AMS-2418
088	TERMINAL	BRIGHT TIN-LEAD	0.000300"MIN. BRIGHT TIN-LEAD (Sn93%-Pb7%) PER ASTM B545 OVER 0.000100"MIN. COPPER PER SAE-AMS-2418

TOLERANCES:\*

DECIMAL	FRACTIONAL	ANGULAR	DRAWING ORIGATION DATE	LAST MODIFICATION DATE
± 0.005	± 1/64	± 5 °	5/31/2002	3/1/2017

\*All dimensions are in inches.

RoHS COMPLIANCE:

09-0163-3-XX

PART NUMBER	RoHS COMPLIANT
09-0163-3-01	YES
09-0163-3-03	YES
09-0163-3-035	YES
09-0163-3-04	YES
09-0163-3-044	YES
09-0163-3-05	NO
09-0163-3-088	NO

09-0163-4-XX

PART NUMBER	RoHS COMPLIANT
09-0163-4-01	YES
09-0163-4-03	YES
09-0163-4-035	YES
09-0163-4-04	YES
09-0163-4-044	YES
09-0163-4-05	NO
09-0163-4-088	NO

09-0163-6-XX

PART NUMBER	RoHS COMPLIANT
09-0163-6-01	YES
09-0163-6-03	YES
09-0163-6-035	YES
09-0163-6-04	YES
09-0163-6-044	YES
09-0163-6-05	NO
09-0163-6-088	NO

TOOLING:

INSTALLATION TOOL: ARBOR PRESS	INSTALLATION TOOL: ANVIL (ARBOR PRESS OPERATED)	INSTALLATION TOOL: PRESS-FIT / ROLL SWAGE / RIVET PUNCH (ARBOR PRESS OPERATED)	INSTALLATION TOOL: FLARE SWAGE PUNCH (ARBOR PRESS OPERATED)
N/A	N/A	N/A	N/A

NOTES:

DATASHEET NOTES
N/A

Continued on next page...

**NOTES** CONTINUED:

---

---

**INSTRUCTION NOTES**

NUT AND WASHER ARE NOT INCLUDED.

---